



CITY OF DANBURY
6102 5TH ST ♦ P.O. BOX 258
DANBURY, TEXAS 77534
PHONE: (979) 922-1551 ♦ FAX: (979) 922-1808



Pool/Spa Construction Permit Application

Project Information			
Project Type (please check one):	<input type="checkbox"/> Pool	<input type="checkbox"/> Spa	<input type="checkbox"/> Pool and Spa
Job Address:		Subdivision:	
Project Valuation:			

Property Owner Information	
Owner:	Phone #:
Address:	City/State/ZIP:

Contractor Information	
Contractor:	Contact Name:
Address:	City/State/ZIP:
Email:	Phone:

Applicant Information	
Applicant is (please check one):	<input type="checkbox"/> Owner <input type="checkbox"/> Contractor <input type="checkbox"/> Other:
Applicant Name (print):	
Applicant Signature:	Date:

Permit and Inspection Information	
Submittal Requirements (other plans maybe necessary depending on complexity of project)	
1. Completed Application	
2. Site Plan showing pool placement in relation to property lines, septic systems and spray heads (if applicable), pool equipment and all other structures on the property.	
3. Pool Plan showing the deck drainage, pool drainage, overflow drainage and sanitary sewer connection (if applicable).	
A permanent Pool Safety Barrier (fence) is required prior to final inspection.	
Required inspections for swimming pools are listed below:	
1. Belly Steel & Bond	
2. Deck Steel & Bond	
3. Underground Electric	
4. Final	
OFFICE USE ONLY BELOW	
Stamp Received/Approved	Permit #:
	Issue Date:
	Final Date:
	Total Fee Paid:

POOL SAFETY BARRIERS TO BE IN PLACE PRIOR TO FINAL POOL INSPECTION.

1) INSTALL A 30 SECOND ALARM ON ALL DOORS THAT OPEN TO POOL YARD. USE A UL 2017 LISTED ALARM.

2) FENCE MUST BE A MINIMUM HEIGHT OF 48", CANNOT HAVE GAPS LARGE ENOUGH FOR A SPHERE FOUR INCHES IN DIAMETER TO PASS THROUGH, ALL PERSONNEL GATES TO BE OUTWARD SWINGING, SELF CLOSING/SELF LATCHING AND ALL LATCHES TO BE MIN 60" ABOVE EXTERIOR GRADE FOR NON-POOL SIDE AND MIN OF 3" BELOW TOP OF FENCE ON POOL SIDE.

3) SUCTION ENTRAPMENT AVOIDANCE FOR POOLS AND SPAS SHALL BE PROVIDED IN ACCORDANCE WITH APSP 7.

4) ALL WINDOWS 60" OR LESS TO WATER'S EDGE REQUIRED TO HAVE SAFETY GLAZING.

5) POOL BACKWASH LINE TO BE CONNECTED TO THE SANITARY SEWER THROUGH A P-TRAP.

6) POOL MUST BE LOCATED A MINIMUM OF 5' FROM SEPTIC TANKS AND 25' FROM THE OUTER EDGE OF THE SEPTIC SPRAY ZONE.

7) IF POOL IS HEATED, AN ON-OFF SWITCH SHALL BE INSTALLED ON THE HEATER.

8) HEATERS AND PUMP MOTORS SHALL BE ON A TIME SWITCH.

9) HEATED POOLS AND SPAS SHALL BE PROVIDED WITH A VAPOR RETARDENT COVER.

**PLANS MUST BE ON SITE
FOR ALL INSPECTIONS**